



DIMENSIONS

		BM 150 TD	BM 200 TD	BM 250 TD	BM 330 TD	BM 400 TD	BM 500 TD	BM 600 TD	BM 700 TD	BM 1100 TD
A	Width	1350	1560	1560	1670	1780	1865	2010	2160	2280
B	Depth	660	660	860	860	860	1075	1075	1075	1305
C	Height	645	645	800	800	800	1033	1033	1033	1250

The concrete mixer bucket M3 model TD is equipped with: safety grill with bag splitter - BOTTOM and bolted HELIX made of wear resistant steel 450 HBW - hydraulic motor fully protected - chain tensioner - electric valve with hydraulic hoses - electric connection kit -hydraulic hoses - flat face couplings (only for SSL) - hydraulic opening of the bottom through a cylinder with covered rod - manually-operated side discharge - unloading pipe L=1500 mm - side chute extension – coupling to the machine (standard bolted bracket starting from mod. BM500TD).

By matching the mixing bucket to compact loaders, please consider the following: the operating load of the machine \geq the full load weight of the mixer bucket.

OPTIONALS

	Bolted bracket	Electric spring winder
Excavator bracket - direct coupling		



MODEL	BM 150 TD	BM 200 TD	BM 250 TD	BM 330 TD	BM 400 TD	BM 500 TD	BM 600 TD	BM 700 TD	BM 1100 TD
Class	1	1	2	2	2	3	3	3	4
Capacity [L]	150	200	250	330	400	500	600	700	1100
Transmission	chain	chain	chain	chain	chain	chain	chain	chain	chain
Empty weight [kg]	310	335	435	455	480	720	740	790	1060
Full load weight [kg]	670	815	1035	1247	1440	1920	2180	2470	3700
Min/max flow rate [L/min]	30/60	30/60	40/75	35/75	35/75	70/150	70/150	70/150	100/115
Max pression cont/peak [bar]	175/225	175/225	175/225	210/300	210/300	150/310	150/310	150/310	205/330

