



DIMENSIONS

	MHC5 160	MHC5 180	MHC5 200	MHC10 160 HD	MHC10 180 HD
Width	1820	2020	2220	2000	2200
Depth	1200	1200	1200	1000	1000
Height	1100	1100	1100	1600	1600

- Cutting diameter: 8 cm 25 cm (HD series only)
- Hydraulic motor with belt transmission
- MKF knives rotor
- MHF hammers rotor

The M3 MHC series bush cutter, featured by its solidity, is designed to fit skid loaders, wheel loaders and telehandlers up to 80/90 HP. Available in 2 versions, standard and HD. **The standard version** is equipped with universal oscillating and floating coupling, mechanical side movement, valve block, sturdy and reinforced structure, helical rotor with tempered hammers (standard) or knives (optional), hydraulic motor with V-belt transmission. **The HD version** is equipped with universal fixed coupling, rotor with fixed widia teeth, reinforced wear-resistant structure, pressure gauge for working pressure control, double rear chains for greater protection, piston motor and high performance HTD single belt transmission. **Drain is recommended for counterpressures > 5 bar.** Rotation speed 2200/2500 rpm.

OPTIONALS	Hydraulic side shifter	Electrovalve
Hydraulic hoses	Coupling for wheel loaders, backhoe loaders, telehandlers	Variable dispacement pisto motor









MODEL	MHC5 160	MHC5 180	MHC5 200	MHC10 160 HD	MHC10 180 HD
Working width [mm]	1600	1800	2000	1600	1800
Weight [kg]	890	930	970	1285	1420
Oil flow [L/min]	60/100	60/100	60/100	100/180	100/180
Pression [bar]	200/220	200/220	200/220	200/350	200/350
Skid loader class [hp]	50/90	50/90	50/90	70/120	70/120
Rotor standard	MHF16	MHF16	MHF16	MHF14	MHF14
Rotor optional	MKF3	MKF3	MKF3	MHF15	MHF15
Motor type	cast iron gear motor			piston motor	
Hammers/Knives number [n°]	18	20	22	42	54

