



DIMENSIONS

		MH3 70	MH3 90	MH5 105	MH7 105	MH7 125	MH11 130	MH11 160
A	Width	950	1150	1300	1250	1450	1450	1850
B	Depth	550	550	600	750	750	900	1000
C	Height	450	450	400	500	500	600	700

The Hydraulic Mulcher STD M3 is designed with a strong and reliable structure and can easily fit any type of excavators. It is manufactured in different models, depending on the use and size of the excavator. It is supplied complete with hydraulic motor, levelling roller with adjustable height, direct transmission (up to MH7), belt transmission (MH11), anti-cavitation valve, priority shockproof valve, adjustable support slides and drilled flat plate. **Drain is recommended for counter-pressures > 5 bar.** Rotation speed 2200/2500 rpm.

OPTIONALS

	Floating system	Hydraulic hoses
Support roller	Bracket	Front and rear chain protection (MH5 only front)



MODEL	MH3 70	MH3 90	MH5 105	MH7 105	MH7 125	MH11 130	MH11 160
Working width [mm]	700	900	1050	1050	1250	1300	1600
Weight [kg]	130	150	190	220	250	345	420
Oil flow [L/min]	20/40	30/40	40/60	60/80	60/80	60/90	80/90
Pression [bar]	170/220	170/220	170/220	200/220	200/220	200/220	200/220
Excavator class [T]	1,5-5,0	2,0-5,0	4,0-6,0	6,0-8,0	6,0-8,0	6,0-12,0	10,0-12,0
Rotor standard	MHF2	MHF2	MHF2	MHF3	MHF3	MHF6	MHF6
Rotor optional	MHC1 / MKC1	MHC1 / MKC1	MHC1 / MKC1	MKF3	MKF3	MKF7	MKF7
Motor type	gears			cast iron gear motor*			
Hammers/knives number [n°]	12	16	16	16	20	20	20

* Upon request, a piston motor is available too